

Axilat™ DF 770 DD is a foam control agent based on a mixture of mineral oil and nonionic surfactants on an inert carrier. It is APEO free.

For further information regarding this product please refer to:

Thomas Fachinger

Phone: +49(0)6181-9880094

eMail: thomas.fachinger@synthomer.com

Property	Typical Value	Unit	Method ¹
Appearance	White powder		TM 436
Oversized particle retained on 22 mesh	< 5	%	
Dispersion (aq)	Disperses in water		TM 415
Specific Gravity	0.6	g/cm ³	

¹ internal method based upon the specified norm

Application Advice

Suggested dosage for some typical applications:

Self-leveling underlayments: 0.1 – 0.3%

Fibre-containing screeds: 0.1 – 0.3%

Cement-based adhesives: 0.1 – 0.3% .

For additional information please contact our Technical Service team.

Axilat DF 770 DD should be used as received and added to the mortar blend.

Delivery form: powder

Advantages

Stable under acidic and alkaline conditions

Excellent defoaming action

Fast acting

Efficient at low dose rates

Very fine Granulation, easily blended with powders

Shipping and Storage

Keep container tightly closed and store in a cool dry place between 5° and 35°C. For Europe, we recommend that the storage time should not exceed 12 months in unopened bags from receipt of delivery. For export, we recommend that the storage time should not exceed 12 months in unopened bags from date of loading on the vessel at the european port.

Product Safety

Before handling, please read the Safety Data Sheet of this product for advice on safety, use and disposal.