

EMULTEX™ 8200 is a fine to medium particle sized colloid stabilised vinyl acetate Veova 10 polymer dispersion with good pigment binding power.

Based on APEO free surfactants, EMULTEX™ 8200 confers excellent application and performance characteristics in a wide range of interior emulsion paints. It is specifically designed to give high sheen with a “soft feel” finish in premium interior sheen coatings, or textured coatings.

For further information regarding this product please refer to:

Coatings Synthomer

eMail: coatings@synthomer.com

Property	Typical Value	Unit	Method ¹
Total solid content	55 ± 1	%	
pH	4.0 - 6.0		
Viscosity	1,000 – 2,000	cps	Brookfield (3/30rpm/25°C)
Minimum film forming temperature	14	°C	
Glass transition temperature [Tg]	19	°C	
Particle size (average)	0.4	µm	

¹ internal method based upon the specified norm

Key Advantages

- Improved wet scrub resistance with Veova “umbrella effect”
- Colloid stabilized giving good opacity
- Good all round performance
- Based on non APEO containing surfactants
- Does not contain formaldehyde based biocide

Shipping and Storage

To ensure maximum stability and maintain optimum polymer dispersion properties, EMULTEX™ 8200 should be stored in closed containers at a temperature between 5°C and 32°C, away from heat sources and direct sunlight. All storage should conform to local fire and building codes.

When properly stored, EMULTEX™ 8200 will remain stable for 6 months from date of delivery.

Product Safety

Before handling, please read the Safety Data Sheet of this product for advice on safety, use and disposal.