

EMULTEX A 5548 is a polyvinyl alcohol stabilised vinyl acetate homopolymer dispersion.

For further information regarding this product please refer to:

Adhesive Polymers (EMEA)

eMail: Adhesive-polymers-EMEA@synthomer.com

Property	Typical Value	Unit	Method ¹
Solids Content	38.0	%	DIN EN ISO 3251
pH Value	5.0		DIN ISO 976
Viscosity (Brookfield RVT 20rpm, @ 23°C)	10000	mPas	DIN ISO 1652
Minimum Film Forming Temperature [MFFT]	2	°C	DIN ISO 2115

¹ internal method based upon the specified norm

Application Advice

EMULTEX A 5548 has been designed specifically for use in school glue.

It can also be used in the building industry as a high performance bonding agent, an additive for concrete and plasters and as a wood adhesive.

Shipping and Storage

Store at an even temperature of between +5°C and +35°C avoiding frost and direct sunlight. Stir product before use. If stored according to these conditions and in the original unopened containers, the dispersion will be stable for 12 months following delivery. Product should be used as soon as possible after opening. During processing, storage and transport, avoid any contact with metals (including non-ferrous metals) which are not protected against corrosion. Detailed information is available on request.

Product Safety

Before handling, please read the Safety Data Sheet of this product for advice on safety, use and disposal.