

LIPATON L 8262 is an aqueous styrene butadiene copolymer dispersion that is APEO free. This dispersion gives plasticising properties in cementitious systems. It also improves adhesion on various substrates.

For further information regarding this product please refer to:

Thomas Fachinger

Phone: +49(0)6181-9880094

eMail: thomas.fachinger@synthomer.com

Property	Typical Value	Unit	Method ¹
Solids content	50,0	%	ISO 1625
pH	7,5		ISO 1148
Viscosity (Brookfield RVT)	< 200	mPas	ISO 2555
Particle size	0,15	µm	Internal method
MFFT	0	°C	ISO 2115
Freeze / Thaw stability	Yes		ISO 1147

¹ internal method based upon the specified norm

Application Advice

- Mortar
- Render
- Gypsum
- Self levelling underlayments
- Screeds
- Primer

LIPATON L 8262 improves also adhesion on various substrates. Further improvements are shock and abrasion resistance (with addition of antifoam), and flexibility. For each new formulation, compatibility between the finished product and the substrate should always be checked.

For additional information please contact our Technical Service Team.

Shipping and Storage

Store at an even temperature of between +5°C and +35°C avoiding frost and direct sunlight. If stored according to these conditions and in the original unopened containers, the dispersion will be stable for 6 months following delivery. Product should be used as soon as possible after opening. During processing, storage and transport, avoid any contact with metals (including non-ferrous metals) which are not protected against corrosion.

- Agitate well before use.
- Detailed information is available on request.

Product Safety

Before handling, please read the Safety Data Sheet of this product for advice on safety, use and disposal.