TECHNICAL DATA SHEET

LIPATON™ SB 65B20

LIPATON™ SB 65B20 is carboxylated styrene-butadiene copolymer designed for liquid membrane application. Superior flexibility and crack-bridging performances. Low VOC. Solvent and plasticizer free. Fulfils ETAG 022 and DIN EN 14891.

For further information regarding this product please refer to:

Construction Synthomer

eMail: Construction@synthomer.com

Property	Typical Value	Unit	Method[1]
Total Solids	50.0	%	DIN EN ISO 3251
pH	8.5		DIN ISO 976
Viscosity (Brookfield LVT @ 23 °C)	150	mPas	DIN ISO 1652
Minimum film forming temperature (MFFT)	0	°C	DIN ISO 2115

[1] internal method based upon the specified norm

Application Advice

LIPATON SB 65B20 is suitable as a binder to formulate very flexible single component liquid applied damp proof membranes. The main application is for membrane systems used beneath ceramic tiles.

For additional information please contact our technical service team.

Shipping and Storage

Store at an even temperature of between +5°C and +35°C avoiding frost and direct sunlight. Stir product before use. If stored according to these conditions and in the original unopened containers, the dispersion will be stable for 6 months following delivery. Product should be used as soon as possible after opening. During processing, storage and transport, avoid any contact with metals (including non-ferrous metals) which are not protected against corrosion.
Detailed information is available on request.

Product Safety

Before handling, please read the Safety Data Sheet of this product for advice on safety, use and disposal.

Disclaimer: This information or data and any other advice or recommendations given or made by us (collectively "Information") are not intended to, nor do they, constitute professional advice or services. Information is provided "AS IS" and on an "AS AVAILABLE" basis and without warranty. We do not warrant or accept responsibility for the accuracy, timeliness or completeness of the Information or data or its suitability for a particular purpose. Synthomer makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Synthomer disclaims (i) any and all liability arising out of the application or use of any product (including as to infringement of third party intellectual property rights), (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability. Any Information concerning any possible use or application of Synthomer products is given by us in good faith and it is entirely for you to satisfy yourself fully as to the suitability of Synthomer products for any particular purpose. Synthomer products are sold in accordance with Synthomer's standard terms and conditions of sale which are available from www.synthomer.com/tc.