

PLEXTOL R 5335 is a fine particle size, surfactant stabilised aqueous acrylic copolymer dispersion. PLEXTOL R 5335 offers high gloss, excellent adhesion and high water resistance.

PLEXTOL R 5335 is recommended for high performance trim paints and wood stains.

For further information regarding this product please refer to:

Dirk Sühling

Phone: +49 2365 49 6796

eMail: dirk.suehling@synthomer.com

Property	Typical Value	Unit	Method <sup>1</sup>
Total Solids	46.0	%	ISO 3251
pH	8.5	-	ISO 976
Viscosity @ 23°C	550	mPa.s	ISO 2555
Tg	15	°C	
Minimum Film Forming Temperature	14	°C	
Ionic Character	anionic		

<sup>1</sup> internal method based upon the specified norm

## Key Advantages

- Very good gloss retention
- Excellent outdoor durability
- Excellent adhesion on several substrates
- Very good water resistance
- APEO free

## Processing

- This product may show discoloration if formaldehyde containing or formaldehyde releasing additives (like biocides) are used. For more information on this product, please contact our Technical Service team.

## Shipping and Storage

This product is supplied in road tankers or in non-returnable plastic drums secured by a lid with clamping ring or in non-returnable palletized bulk containers (net volume 1.000 lt). The product must be protected from frost and exposure to direct sunlight. Storage temperatures between +5 °C and +30 °C are recommended. The product contains in-can preservation to protect it against microbiological attack during transportation. For protection against microbiological contamination during storage stringent plant hygiene is essential. Depending on the storage conditions addition of suitable preservatives may be necessary. Care must be taken that drums and containers are properly closed. During storage, shipping and handling contact with metal surfaces that are not corrosion protected must be avoided. When stored properly, the product has a shelf life of 12 months from the date of delivery.

## Product Safety

Before handling, please read the Safety Data Sheet of this product for advice on safety, use and disposal.