PLIOLITE™ VTAC-L

PLIOLITE™ VTAC-L is a highly soluble, vinyl toluene-acrylate copolymer that forms tough, durable films with excellent adhesion to concrete and steel, with very good water and chemical resistance.

Newtonian resin soluble in mineral spirits, for formulation of flat or textured masonry coatings, alkali resistant primers, anticorrosion paints and intumescent coatings.

For further information regarding this product please refer to:

Coatings Synthomer

eMail: coatings@synthomer.com

Property	Typical Value	Unit	Method[1]
Solubility, Solvent KB	36		
Color	White		
Physical Form	Friable Granules		
Tg (Midpoint)	58	°C	
Cup Viscosity (Ford Cup #4 @25°C, 25% in white spirit 17)	25	sec	
Density	8.6	lb/gal	
Specific Gravity	1.03	g/cm³	
Rheology	Newtonian		

[1] internal method based upon the specified norm

Key Advantages

- Forms tough, durable films
- Excellent adhesion to masonry and concrete
- High solubility, good sprayability
- Compatible with modifying resins and plasticisers such as: Hydrocarbons, styrene derivatives, rosins, silicones, vegetable oils, esters, chlorinated paraffins, urea derivatives and aromatic oils

Shipping and Storage

Available packaging : Pallet 500 Kg with 25 Kg antistatic bags

Recommended Storage conditions : Store in a dry, well ventilated area.

Shelf life : 36 months minimum from date of manufacture when stored in recommended conditions.

Product Safety

Before handling, please read the Safety Data Sheet of this product for advice on safety, use and disposal.

Disclaimer: This information or data and any other advice or recommendations given or made by us (collectively "Information") are not intended to, nor do they, constitute professional advice or services. Information is provided "AS IS" and on an "AS AVAILABLE" basis and without warranty. We do not warrant or accept responsibility for the accuracy, timeliness or completeness of the Information or data or its suitability for a particular purpose. Synthomer makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Synthomer disclaims (i) any and all liability arising out of the application or use of any product (including as to infringement of third party intellectual property rights), (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability. Any Information concerning any possible use or application of Synthomer products is given by us in good faith and it is entirely for you to satisfy yourself fully as to the suitability of Synthomer products for any particular purpose. Synthomer products are sold in accordance with Synthomer's standard terms and conditions of sale which are available from www.synthomer.com/tc.