

PLIOWAY™ Ultra 200 is a substituted styrene-acrylate copolymer soluble in odourless isoparaffinic solvents, that forms non-yellowing, tough coatings with excellent adhesion and stain blocking properties.

Highly soluble Newtonian resin for formulation of odourless stain blocking primers, basement water proofing sealers, correction fluids and intumecent coatings.

For further information regarding this product please refer to:

Coatings Synthomer

eMail: coatings@synthomer.com

Property	Typical Value	Unit	Method ¹
Solubility, Solvent KB	28		
Color	White		
Physical Form	Friable Granules		
Tg (midpoint)	57	°C	
Cup Viscosity (Ford Cup #4 @25°C, 25% in Isopar G)	30	sec	
Density	8.59	lb/gal	
Specific Gravity	1.03	g/cm ³	
Rheology	Newtonian		

¹ internal method based upon the specified norm

Key advantages

- Forms tough, durable films
- Excellent adhesion to most substrates without primer
- Blocks most stains in one coat
- Efflorescence resistant
- Direct application on solvent sensitive plastics such as polystyrene tiles
- Non-yellowing in the dark

Shipping and Storage

Available packaging : Pallet 500 Kg with 25 Kg antistatic bags

Recommended Storage conditions : Store in a dry, well ventilated area.

Shelf life : 36 months minimum from date of manufacture when stored in recommended conditions.

Product Safety

Before handling, please read the Safety Data Sheet of this product for advice on safety, use and disposal.

