

PLIOWAY™ Ultra 350LV is a substituted styrene-acrylate copolymer, soluble in odourless isoparaffinic solvents, that form tough, non-yellowing with excellent adhesion and stain blocking properties.

Low viscosity Newtonian resin for formulation of odourless stain blocking primers, basement water proofing sealers, correction fluids, and intumescent coatings.

For further information regarding this product please refer to:

Coatings Synthomer

eMail: coatings@synthomer.com

Property	Typical Value	Unit	Method ¹
Solubility, Solvent KB	28		
Color	White		
Physical Form	Friable Granules		
Tg (midpoint)	49	°C	
Cup Viscosity (Ford Cup #4 @25°C, 25% in Isopar G)	15	sec	
Density	8.59	lb/gal	
Specific Gravity	1.03	g/cm ³	
Rheology	Newtonian		

¹ internal method based upon the specified norm

Key advantages

- Tension-free film formation, ideal for renovation
- Excellent adhesion to most substrates without primer
- Blocks most stains in one coat
- Direct application on solvent sensitive plastics such as polystyrene tiles
- Low viscosity at high solid levels
- Fast drying and odorless; can apply two coats in one day

Shipping and Storage

Available packaging : Pallet 500 Kg with 25 Kg antistatic bags

Recommended Storage conditions : Store in a dry, well ventilated area.

Shelf life : 36 months minimum from date of manufacture when stored in recommended conditions.

Product Safety

Before handling, please read the Safety Data Sheet of this product for advice on safety, use and disposal.