

REVACRYL™ DS 2100 is an ammonia free, water-based dispersion of a styrene-acrylic copolymer. It can be used in a broad range of coating applications with well-balanced performance envelope.

It's suitable for formulation of indoor mat, silk and semi-gloss paints and Masonry facade paints, with or without silicone emulsion.

For further information regarding this product please refer to:

Coatings Synthomer

eMail: coatings@synthomer.com

Property	Typical Value	Unit	Method ¹
Solid content	50	%	ISO 3251
pH	8.0		ISO 976
Viscosity (RVT)	1250	mPa.s	ISO 2555
MFFT	18	°C	ISO 2115
Specific Gravity	1.02	g/cm3	ISO 2811

¹ internal method based upon the specified norm

Application Advice

REVACRYL™ DS 2100 has a high pigment binding power with very good water and saponification resistance.

REVACRYL™ DS 2100 is an excellent multipurpose product for matt interior, satin and semi-gloss paints and other interior and exterior coatings.

Shipping and Storage

This product is supplied in road tankers or in non-returnable plastic drums secured by a lid with clamping ring or in non-returnable palletized bulk containers (net volume 1.000 lt). The product must be protected from frost and exposure to direct sunlight. Storage temperatures between +5 °C and +30 °C are recommended. The product contains in-can preservation to protect it against microbiological attack during transportation. For protection against microbiological contamination during storage stringent plant hygiene is essential. Depending on the storage conditions addition of suitable preservatives may be necessary. Care must be taken that drums and containers are properly closed. During storage, shipping and handling contact with metal surfaces that are not corrosion protected must be avoided. When stored properly, the product has a shelf life of 6 months from the date of delivery.

Product Safety

Before handling, please read the Safety Data Sheet of this product for advice on safety, use and disposal.