

REVACRYL AG 204 is an ammonia free aqueous dispersion of a styrene-acrylic copolymer that is suitable for agricultural applications.

For further information regarding this product please refer to:

Christophe Baude

Phone: +33 1 6929 2733

eMail: christophe.baude@synthomer.com

| Property | Typical Value | Unit | Method ¹ |
|----------------------------|---------------|------|---------------------|
| Solid content | 48 | % | ISO 3251 |
| pH | 8.5 | | ISO 976 |
| Viscosity (Brookfield RVT) | 80 | mPas | ISO 2555 |
| MFFT | 1 | °C | internal method |

¹ internal method based upon the specified norm

Shipping and Storage

This product is supplied in road tankers or in non-returnable plastic drums secured by a lid with clamping ring or in non-returnable palletized bulk containers (net volume 1.000 lt). The product must be protected from frost and exposure to direct sunlight. Storage temperatures between +5 °C and +30 °C are recommended. The product contains in-can preservation to protect it against microbiological attack during transportation. For protection against microbiological contamination during storage stringent plant hygiene is essential. Depending on the storage conditions addition of suitable preservatives may be necessary. Care must be taken that drums and containers are properly closed. During storage, shipping and handling contact with metal surfaces that are not corrosion protected must be avoided. When stored properly, the product has a shelf life of 6 months from the date of delivery.

Product Safety

Before handling, please read the Safety Data Sheet of this product for advice on safety, use and disposal.