

Durable hydrophilic finishing treatment for nonwovens

For further information regarding this product please refer to:

Consumer Materials Synthomer

eMail: consumer.materials@synthomer.com

Property	Typical Value	Unit	Method ¹
Chemistry Type	other		
Solids Content	34.5	%	EN ISO 3251
pH Value	7.5		DIN ISO 976
Color	tan/translucent		intern
Density	8.3	lb/gal	

¹ internal method based upon the specified norm

Application Advice

SoftWick SF30 hydrophilic durable finishing treatment provides wicking properties for improved fluid management and softness for comfort for synthetic and cellulosic nonwoven fabrics.

- Imparts superior wicking properties to nonwoven fabrics for improved fluid management
- Imparts softness onto nonwovens fabric for comfort
- Rapid strike-through
- Non-migratory and durable single treatment for both wicking and softness
- Compatible with typical finishing systems including kiss roll, spray, and saturation
- Very effective at low add-on levels
- Dilutes readily with water to form a stable bath

Shipping and Storage

This product is supplied in road tankers or in non-returnable plastic drums or in totes (IBC). The product must be protected from frost and exposure to direct sunlight. Storage temperatures between +5 °C and +30 °C are recommended. Care must be taken that drums and containers are properly closed. During storage, shipping and handling contact with metal surfaces that are not corrosion protected must be avoided. When stored properly, the product has a shelf life of 12 months from the date of delivery. - Mix the contents thoroughly before using. - This product is not freeze-thaw stable.

Product Safety

Before handling, please read the Safety Data Sheet of this product for advice on safety, use and disposal.