

Synthebond 7803 is a water-based, coater-ready acrylic pressure-sensitive adhesive designed for paper label applications.

For further information regarding this product please refer to:

Adhesive Polymers (Americas)

eMail: Adhesive-polymers-Americas@synthomer.com

Property	Typical Value	Unit	Method ¹
Solids Content	44	%	
Viscosity (Brookfield RVT 3/20)	250	cP	
pH	7.8		
Density	8.6	lb/gallon	

¹ internal method based upon the specified norm

Application Advice

Synthebond 7803 has been formulated for reverse gravure coating operations. Synthebond 7803 is designed to provide low energy substrate wetting, and a balance of peel and shear properties.

Recommended applications include paper labels for:

- wine and spirit bottles
- health and beauty applications
- other specialty applications

Shipping and Storage

Store at an even temperature of between +5°C and +35°C avoiding frost and direct sunlight. Stir product before use. If stored according to these conditions and in the original unopened containers, the dispersion will be stable for 6 months following delivery. Product should be used as soon as possible after opening. During processing, storage and transport, avoid any contact with metals (including non-ferrous metals) which are not protected against corrosion. Detailed information is available on request.

Product Safety

Before handling, please read the Safety Data Sheet of this product for advice on safety, use and disposal.