

SYNTHEBOND™ SC 171 hydrophobic non-silicone release polymer is suitable to be used as a release primer for flooring adhesives.

For further information regarding this product please refer to:

Construction Synthomer

eMail: Construction@synthomer.com

Property	Typical Value	Unit	Method ¹
Total Solids Content	40.0	%	EN ISO 3251
pH Value	6.0		DIN ISO 976
Viscosity (RVT, S2, 20 rpm, 25°C)	< 250	mPa·s	ISO 1652
Ionic Character	nonionic		
Release Level	medium		

¹ internal method based upon the specified norm

Application Advice

SYNTHEBOND™ SC 171 is hydrophobic non-silicone release vinyl acrylic polymer, which is suitable to be used as a release primer for flooring adhesives.

- Non-silicone release chemistry
- Formulated with no APEOs or fluorochemicals
- Very good humidity and water resistance
- Good release aging properties

For additional information, please contact our Technical Service team.

Shipping and Storage

The product must be protected from frost and exposure to direct sunlight. Storage temperatures between +5 °C and +30 °C are recommended. Care must be taken that drums and containers are properly closed. During storage, shipping and handling contact with metal surfaces that are not corrosion protected must be avoided. When stored properly, the product has a shelf life of 6 months from the date of delivery. Mix the contents thoroughly before using.

Product Safety

Before handling, please read the Safety Data Sheet of this product for advice on safety, use and disposal.