

Synthebond E 4010 is a styrene acrylic copolymer of use in a variety of adhesive applications.

For further information regarding this product please refer to:

Lim Kee Guan

Phone: +603 2080 7231

eMail: keeguan.lim@synthomer.com

Property	Typical Value	Unit	Method ¹
Total Solids Content (TSC)	49 - 51	%	EM / 01
Viscosity (Brookfield, LVT#2/60rpm)	max 500	cP	EM / 03
pH	8 - 9		EM / 02
Grit content (#300)	200 max	ppm	EM / 37

¹ internal method based upon the specified norm

Application Advice

Synthebond E 4010 was designed with excellent alkali resistance and is compatible with a large variety of other formulating ingredients such as fillers, pigments, and dyes

Synthebond E 4010 is made based on non APEO containing surfactants.

Shipping and Storage

Store at an even temperature of between +5°C and +35°C avoiding frost and direct sunlight. Stir product before use. If stored according to these conditions and in the original unopened containers, the dispersion will be stable for 6 months following delivery. Product should be used as soon as possible after opening. During processing, storage and transport, avoid any contact with metals (including non-ferrous metals) which are not protected against corrosion. Detailed information is available on request.

Product Safety

Before handling, please read the Safety Data Sheet of this product for advice on safety, use and disposal.