TECHNICAL DATA SHEET

Synthomer™ Ester Gum 8D RSPO Resin



Revision: 29.05.2024 Page 1 of 2

SYNTHOMER™ Ester Gum 8D RSPO Resin is the glycerol ester of gum rosin produced using glycerin derived from RSPO-certified palm oil (Roundtable on Sustainable Palm Oil). A special process yields a pale, low-odor, low-acid-number product. In most countries SYNTHOMER™ Ester Gum 8D RSPO Resin has clearance as a masticatory ingredient in chewing gum compositions.

For further information regarding this product please refer to:

Synthomer Adhesive Technologies

eMail: Adhesive.Technologies@Synthomer.com

- · Broad compatibility and solubility
- Low acid number
- Low odor and taste
- · Medium softening point
- · Thermoplastic resin

| Property | Typical Value | Unit | Method ¹ |
|-------------------------------|-----------------------------|----------|------------------------------------|
| Description, Base Resin | Glycerol Ester of Gum Rosin | | |
| Ring and Ball Softening Point | 89 | °C | ASTM E 28 |
| Color, Gardner | 7 | | ASTM D 6166, 50% solids in toluene |
| Acid Number | 7 | mg KOH/g | ASTM D 465 |
| Density at 25°C | 1.08 | kg/dm³ | |

¹ internal method based upon the specified norm

Applications

Food Additives

Compatibility and Solubility

Compatible with natural rubber, synthetic rubbers, Ethylcellulose, Polystyrene, many natural and synthetic resins, waxes and most vinyl resins.

Soluble in aromatic hydrocarbons, aliphatic hydrocarbons, esters, ketones and carbon tetrachloride. Insoluble in Methanol and Ethanol.

Solubility Parameters, 50% resin concentration. 7,0-10,6 in Class I solvents - weakly hydrogen-bonded; 7,4-10,5 in Class II solvents - moderately hydrogen-bonded; 9,5-11,4 in Class III solvents - strongly hydrogen-bonded.

Packaging

SYNTHOMER™ Ester Gum 8D RSPO Resin is supplied in solid pastille form. Material is packed in polyethylene bags of 25 kg net and supplied on shrink-wrapped pallets of 40 bags each (1000 kg) from Synthomer facilities in the Netherlands and from warehouses located in Europe.

Storage

Due to the thermoplastic behavior, pastillated and flaked resins may fuse, block or lump. This can be accelerated under any of the following conditions: 1) above ambient temperature 2) prolonged storage 3) pressure, e.g., stacking pallets, or a combination of these conditions. This is particularly applicable for low softening point resin grades.

In order to maintain the flake or pastille shape, we therefore recommend storing the material in a temperature-controlled area; be careful with stacking material or applying pressure and preventing prolonged storage.

It should be noted that lumping does not have a negative impact on the product specifications. Due to the nature of the product, claims regarding lumping cannot be accepted.

Disclaimer: This information or data and any other advice or recommendations given or made by us (collectively "Information") are not intended to, nor do they, constitute professional advice or services. Information is provided "AS IS" and on an "AS AVAILABLE" basis and without warranty. We do not warrant or accept responsibility for the accuracy, timeliness or completeness of the Information or data or its suitability for a particular purpose. Synthomer makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Synthomer disclaims (i) any and all liability arising out of the application or use of any product (including as to infringement of third party intellectual property rights), (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability. Any Information concerning any possible use or application of Synthomer products is given by us in good faith and it is entirely for you to satisfy yourself fully as to the suitability of Synthomer products for any particular purpose. Synthomer products are sold in accordance with Synthomer's standard terms and conditions of sale which are available from www.synthomer.com/tc.

TECHNICAL DATA SHEET

Synthomer™ Ester Gum 8D RSPO Resin



Revision: 29.05.2024 Page 2 of 2

Resins are prone to gradual oxidation, some more so than others. This could result in darkening and/or it could have an adverse effect on the solubility of the resin in organic solvents or on its compatibility with polymers. Accordingly, it is recommended that strict control of inventory be observed at all times, taking care that the oldest material is used first.

SYNTHOMER™ Ester Gum 8D RSPO Resin material will remain within product specification limits for a period of at least 6 months after shipment from Synthomer production facilities in the Netherlands provided storage conditions outlined in this data sheet are observed.

Comments

Properties reported here are typical of average lots. Synthomer makes no representation that the material in any particular shipment will conform exactly to the values given.