

Tacolyn™ 5070 Resin Dispersion



Tacolyn™ 5070 resin dispersion is an aqueous, 50% solids, solvent-free anionic aliphatic hydrocarbon dispersion prepared from a low molecular weight, aliphatic C5 hydrocarbon resin. It is recommended as a tackifier for isoprene rubber and natural rubber latex polymers used in tape applications. Tacolyn™ 5070 is ideal for low peel applications because it imparts peel strength in small increments relative to resination level. It exhibits good storage and mechanical stability and outstanding stability to acids. Tacolyn™ 5070 is also highly resistant to acids and alkalies.

- Broad utility as a general purpose isoprene and natural rubber tackifier
- Exhibits good storage and mechanical stability
- Highly resistant to acids and alkalies
- Promotes low peel

For further information regarding this product please refer to:

Synthomer Adhesive Technologies

eMail: Adhesive.Technologies@Synthomer.com

Property	Typical Value	Unit	Method ¹
Particle Size	250	nm	Average particle size
Coarse Particles	0.1000	% max	Wt% of particles >45 microns
Ring and Ball Softening Point	70	°C	ASTM E 28, dispersed phase (base resin+emulsifier)
Shelf Life	243	days	
Total solids content	50	%	
pH	4.0		
pH Tolerance Range	4-13		
Viscosity at 25°C	100	cP	Brookfield
Density	0.97	g/mL	

¹ internal method based upon the specified norm

Applications

Adhesives for construction, Carpet, Metal coatings, Tapes, Coatings, Labels, PSA Tapes

Compatibility and Solubility

Compatible with natural rubber latex. When mixed with cationic substances, this dispersion may precipitate. When high alkaline or acidic additives are added to Tacolyn™ 5070, gross localized pH-variations should be avoided, as these can lead to destabilization and grit formation.

Packaging

Available in lined fiber drums (445 lbs/202 kg net wt.), disposable totes or tank trucks. Keep container closed to prevent formation of dried film on container walls. If dry filming occurs, filter product before use.

Storage

The recommended storage temperature range is 50°-100°F. This resin dispersion may be irreparably damaged if frozen. Accordingly, all shipments in cold climate areas are made in insulated or heated carriers. It is recommended that strict control of inventory be observed at all times, taking care that the oldest material is used first.

Disclaimer: This information or data and any other advice or recommendations given or made by us (collectively "Information") are not intended to, nor do they, constitute professional advice or services. Information is provided "AS IS" and on an "AS AVAILABLE" basis and without warranty. We do not warrant or accept responsibility for the accuracy, timeliness or completeness of the Information or data or its suitability for a particular purpose. Synthomer makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Synthomer disclaims (i) any and all liability arising out of the application or use of any product (including as to infringement of third party intellectual property rights), (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability. Any Information concerning any possible use or application of Synthomer products is given by us in good faith and it is entirely for you to satisfy yourself fully as to the suitability of Synthomer products for any particular purpose. Synthomer products are sold in accordance with Synthomer's standard terms and conditions of sale which are available from www.synthomer.com/tc.

Tacolyn™ 5070 Resin Dispersion



The useful life of this product can be affected by storage and handling conditions. This dispersion will remain within product specification limits for at least 243 days from date of manufacture from an Synthomer production facility provided that storage conditions are observed.

Comments

Properties reported here are typical of average lots. Synthomer makes no representation that the material in any particular shipment will conform exactly to the values given.