

Vinaltex™ M35/73 Solution is a copolymer of vinyl acetate and dibutyl maleate dissolved in ethyl acetate.

It is designed for use mainly in solvent based coatings, where it can be diluted for use as a highly efficient primer and sealer.

For further information regarding this product please refer to:

Jack Wheatley

Phone: +44 (0) 1279 741 225

eMail: Jack.Wheatley@synthomer.com

FEATURES

- Miscible with most organic solvents
- Very high resistance to hydrolysis
- Solution polymer
- Rapid penetration and binding
- Excellent low temperature heat seal

Vinaltex™ M35/73 Solution is manufactured on a dedicated polymerisation plant and is produced in the form of a colourless solution.

Property	Typical Value	Unit	Method ¹
Total Solid Content	60.0 ± 1.0	%	MTP1
Viscosity @ 20°C	6.000 - 12.000	mPa.s	MTP10
Density	1.05	g/cm3	
Typical molecular weight	90.000	Da	
Tg	+16	°C	
Flash point	<21	°C	
Appearance	Colourless solution		

¹ internal method based upon the specified norm

Application Advice

Dilution - Vinaltex™ M35/73 Solution is miscible with many organic solvents such as lower alcohols, ketones, aromatic hydrocarbons and esters. Further information on the formulation of Vinaltex™ M35/73 Solution for use as a primer / sealer, is available in the datasheet Stabilising Solutions and Sealers.

Compatibility - Vinaltex™ M35/73 Solution may be combined with other M grades in an appropriate solvent. It is not compatible with water based systems.

Primer & sealer for new masonry & plaster, sealer & binder for restoration of stonework, Sealer for concrete floors, heat seal adhesive formulations.

Shipping and Storage

The product should be stored in a cool, dry place, where care must be taken to keep the containers tightly sealed and to observe regulations on the storage and handling of products containing solvents. Vinaltex™ M35/73 Solution should be stored in sealed containers as received. In this condition the product should remain fit for use for 24 months from the date of manufacture. Beyond that date the material may still be fit for use but we would advise that it is good practice to retest the product before use.

PACKAGING

Disclaimer: This information or data and any other advice or recommendations given or made by us (collectively "Information") are not intended to, nor do they, constitute professional advice or services. Information is provided "AS IS" and on an "AS AVAILABLE" basis and without warranty. We do not warrant or accept responsibility for the accuracy, timeliness or completeness of the Information or data or its suitability for a particular purpose. Synthomer makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Synthomer disclaims (i) any and all liability arising out of the application or use of any product (including as to infringement of third party intellectual property rights), (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability. Any Information concerning any possible use or application of Synthomer products is given by us in good faith and it is entirely for you to satisfy yourself fully as to the suitability of Synthomer products for any particular purpose. Synthomer products are sold in accordance with Synthomer's standard terms and conditions of sale which are available from www.synthomer.com/tc.

Vinaltex™ M35/73 Solution is supplied in 60 litre open top lacquer lined steel drums or 220 litre antistatic plastic drums.

Product Safety

Before handling, please read the Safety Data Sheet of this product for advice on safety, use and disposal.