

BEPD 70L is a mixture of 2-Butyl-2-Ethyl-1,3-Propanediol (BEPD), Neopentyl Glycol and water
Clear and colourless liquid at room temperature
Diol containing primary hydroxyl groups

CAS number: 115-84-4, 126-30-7

EC (EINECS) number: 204-111-7, 204-781-0

HS number: 3824 99

For further information regarding this product please refer to:

Head Office Synthomer Limited

Tel: +44 (0)1279 436 211

eMail: info@synthomer.com

Property	Value	Unit	Method ¹
BEPD content	70 ± 1	%	ISO 2718-1974
Neopentyl glycol content	25 ± 1	%	ISO 2718-1974
Water content	5 ± 1	%	ASTM E203-96

¹ internal method based upon the specified norm

Application Advice

- Saturated polyesters for coil, can and powder coatings
- Unsaturated polyesters for gelcoats and composites
- Polyurethanes applications for coatings, adhesives, textiles and accessories
 - As part of Polyesters Polyols
 - Or in the form of a Chain Extender

Shipping and Storage

Storage at room temperature is recommended. Storage at lower temperatures can result in solidification of the product. All drums should be used in their entirety or agitated before use.

Delivery forms

- Bulk in molten form,
- Steel drums 190 Kg, 760 Kg/pallet
- IBC, 940Kg

Product Safety

Before handling, please read the Safety Data Sheet of this product for advice on safety, use and disposal.