

AXILAT™ DF 6352 DD is a foam control agent based on a mixture of mineral oil and nonionic surfactants on an inert carrier. It is APEO free.

For further information regarding this product please refer to:

Thomas Fachinger

Tel: +49(0)6181-9880094

eMail: thomas.fachinger@synthomer.com

Property	Typical Value	Unit	Method ¹
Appearance	White powder		TM 436
Oversized particle retained on 22 mesh	< 5	%	
Dispersion (aq)	Excellent		TM 414
Untapped density	0.5	g/c- ³	

¹ internal method based upon the specified norm

Application Advice

Suggested dosage for some typical applications:

Cement/sand-based mortars: 0.1 – 0.3%

Gypsum-based mortars: 0.1 – 0.4%

Cement-based adhesives: 0.1 – 0.3%

Joint mortars: 0.1 – 0.3%

Repair mortars: 0.1 – 0.3% .

For additional information please contact our Technical Service team.

AXILAT DF 6352 DD should be used as received and added to the mortar blend.

Stable under acidic and alkaline conditions

Efficient at low dose rates

Shipping and Storage

Keep container tightly closed and store in a cool dry place between 5° and 35 °C. Shelf life is 12 months in unopened bags.

Product Safety

Before handling, please read the Safety Data Sheet of this product for advice on safety, use and disposal.