

Axilat™ DF 770 DD is a foam control agent based on a mixture of mineral oil and nonionic surfactants on an inert carrier. It is APEO free.

For further information regarding this product please refer to:

Thomas Fachinger

Tel: +49(0)6181-9880094

eMail: [thomas.fachinger@synthomer.com](mailto:thomas.fachinger@synthomer.com)

Property	Typical Value	Unit	Method <sup>1</sup>
Appearance	White powder		TM 436
Oversized particle retained on 22 mesh	< 5	%	
Dispersion (aq)	Disperses in water		TM 415
Untapped density	0.6	g/cm <sup>3</sup>	

<sup>1</sup> internal method based upon the specified norm

## Application Advice

Suggested dosage for some typical applications:

Self-leveling underlayments: 0.1 – 0.3%

Fibre-containing screeds: 0.1 – 0.3%

Cement-based adhesives: 0.1 – 0.3% .

For additional information please contact our Technical Service team.

Axilat DF 770 DD should be used as received and added to the mortar blend.

Delivery form: powder

Advantages

Stable under acidic and alkaline conditions

Excellent defoaming action

Fast acting

Efficient at low dose rates

Very fine Granulation, easily blended with powders

## Shipping and Storage

Keep container tightly closed and store in a cool dry place between 5° and 35°C. Shelf life is 12 months in unopened bags. Delivery form: powder

## Product Safety

Before handling, please read the Safety Data Sheet of this product for advice on safety, use and disposal.