

Axilat™ DF 775 DD is a foam control agent based on a mixture of mineral oil and nonionic surfactants on an inert carrier. It is APEO free.

For further information regarding this product please refer to:

Thomas Fachinger

Tel: +49(0)6181-9880094

eMail: thomas.fachinger@synthomer.com

Property	Typical Value	Unit	Method ¹
Appearance	White powder		TM 436
Oversized particle retained on 1500 micron	< 5	%	
Dispersion (aq)	Excellent		TM 415

¹ internal method based upon the specified norm

Application Advice

Suggested dosage for some typical applications:

Self-leveling underlayments: 0.1 – 0.3%

Fibre-containing screeds: 0.1 – 0.3%

Cement-based adhesives: 0.1 – 0.3% .

For additional information please contact our Technical Service team.

Axilat DF 775 DD should be used as received and added to the mortar blend.

Delivery form: powder

Advantages

Stable under acidic and alkaline conditions

Excellent defoaming action

Fast acting

Efficient at low dose rates

Very fine Granulation, easily blended with powders

Shipping and Storage

Keep container tightly closed and store in a cool dry place between 5° and 35°C. Shelf life is 12 months in unopened bags. Delivery form: powder

Product Safety

Before handling, please read the Safety Data Sheet of this product for advice on safety, use and disposal.