

EMULTEX 4300 is a compounded, polyvinyl alcohol stabilised, vinyl acetate dibutyl maleate copolymer dispersion.

For further information regarding this product please refer to:

Martin Driever

Tel: +49 173 3179751

eMail: Martin.Driever@synthomer.com

Property	Typical Value	Unit	Method ¹
Solids Content	53,0	%	ISO 3251
pH Value	4,5		ISO 976
Viscosity	< 2000	mPa.s	ISO 2255

¹ internal method based upon the specified norm

Application Advice

EMULTEX 4300 has been designed as binder for the impregnation of polyester and glass fibre fabrics and scrims. After drying, EMULTEX 4300 forms a medium stiff film with good blocking resistance at ambient temperature. At elevated temperatures, the film can be activated and allows sealing of the finished fabrics or scrims to a variety of substrates.

Shipping and Storage

Store at an even temperature of between +5°C and +35°C avoiding frost and direct sunlight. Stir product before use. If stored according to these conditions and in the original unopened containers, the dispersion will be stable for 6 months following delivery. Product should be used as soon as possible after opening. During processing, storage and transport, avoid any contact with metals (including non-ferrous metals) which are not protected against corrosion. Detailed information is available on request.

Product Safety

Before handling, please read the Safety Data Sheet of this product for advice on safety, use and disposal.