

A concentrated surface protectant for use on polished or decorative concrete surfaces

Mor-shine Ultra CSG penetrates into functional concrete surfaces and provides excellent durability and protection from stains and abrasion

For further information regarding this product please refer to:

Lauren Sharpe

Tel: + 1 803 377 2292

eMail: Lauren.Sharpe@synthomer.com

Property	Typical Value	Unit	Method ¹
Chemistry Type	Water-based polymer		
Solids Content	18.0	%	
pH	11.0		
Viscosity [Brookfield LVT #1/20 rpm @25°C]	<15	cps	
Density	8.59	lb/gal	
Crosslinking	Proprietary		
Ionic Character	Anionic		

¹ internal method based upon the specified norm

Key Advantages

- Resistant to most types of stain
- Fast cure time puts floors back in service sooner
- VOC compliant means lower odor
- Excellent hardness and durability for lasting shine
- Repairable for reduced maintenance time and cost
- Attractive high-gloss finish
- Can be used full strength or diluted with water

Shipping and Storage

This product is supplied in road tankers or in non-returnable plastic drums secured by a lid with clamping ring or in non-returnable palletized bulk containers (net volume 1.000 lt). The product must be protected from frost and exposure to direct sunlight. Storage temperatures between +5 °C and +30 °C are recommended. The product contains in-can preservation to protect it against microbiological attack during transportation. For protection against microbiological contamination during storage stringent plant hygiene is essential. Depending on the storage conditions addition of suitable preservatives may be necessary. Care must be taken that drums and containers are properly closed. During storage, shipping and handling contact with metal surfaces that are not corrosion protected must be avoided. When stored properly, the product has a shelf life of 12 months from the date of manufacture.

Product Safety

Before handling, please read the Safety Data Sheet of this product for advice on safety, use and disposal.