

Pliolite AC4 is a styrene-acrylate copolymer, often used in combination with Pliolite AC80, to form tough abrasion and chemically resistant films that have excellent UV resistance and exterior weathering properties.

Solvent based thixotropic resin for low to high textured exterior masonry coatings, primers, anti-corrosion coatings, concrete protection and intumescent coatings.

For further information regarding this product please refer to:

Christophe Baude

Tel: +33 1 6929 2733

eMail: christophe.baude@synthomer.com

Property	Typical Value	Unit	Method ¹
Solubility, Solvent KB	45		
Color	White		
Physical Form	Friable Granules		
Tg [Midpoint]	55	°C	
Brookfield Viscosity (25°C, Sp.6, 10 rpm, 15% in mixed solvent)	68	Pa.s	
Density	8.6	lb/gal	
Specific Gravity	1.03	g/cm ³	
Rheology	Thixotropic		

¹ internal method based upon the specified norm

Key advantages

- Rheological thermoplastic resin
- High hardness
- Excellent adhesion
- Efflorescence resistance
- Alkali resistance
- Superb exterior weathering
- When used with Pliolite AC80 can create thick masonry that can be applied at 200 µm

Shipping and Storage

Available packaging : Pallet 500 Kg with 25 Kg antistatic bags

Recommended Storage conditions : Store in a dry, well ventilated area.

Shelf life : 36 months minimum from date of manufacture when stored in recommended conditions.

Product Safety

Before handling, please read the Safety Data Sheet of this product for advice on safety, use and disposal.