

Plioway Ultra 200 is a vinyl-acrylate copolymer soluble in odourless isoparaffinic solvents, that forms non-yellowing, tough coatings with excellent adhesion and stain blocking properties.

Highly soluble Newtonian resin for formulation of odourless stain blocking primers, basement water proofing sealers, correction fluids and intumescant coatings.

For further information regarding this product please refer to:

Christophe Baude

Tel: +33 1 6929 2733

eMail: christophe.baude@synthomer.com

| Property | Typical Value | Unit | Method ¹ |
|--|------------------|-------------------|---------------------|
| Solubility, Solvent KB | 28 | | |
| Color | White | | |
| Physical Form | Friable Granules | | |
| Tg (midpoint) | 57 | °C | |
| Cup Viscosity (Ford Cup #4 @25°C, 25% in Isopar G) | 30 | sec | |
| Density | 8.59 | lb/gal | |
| Specific Gravity | 1.03 | g/cm ³ | |
| Rheology | Newtonian | | |

¹ internal method based upon the specified norm

Key advantages

- Forms tough, durable films
- Excellent adhesion to most substrates without primer
- Blocks most stains in one coat
- Efflorescence resistant
- Direct application on solvent sensitive plastics such as polystyrene tiles
- Non-yellowing in the dark

Shipping and Storage

Available packaging : Pallet 500 Kg with 25 Kg antistatic bags

Recommended Storage conditions : Store in a dry, well ventilated area.

Shelf life : 36 months minimum from date of manufacture when stored in recommended conditions.

Product Safety

Before handling, please read the Safety Data Sheet of this product for advice on safety, use and disposal.