

Plioway Ultra G20 is a vinyl-acrylate copolymer, soluble in odourless isoparaffinic solvents and used in combination with Plioway Ultra 200 or Ultra 350LV, eliminating the need for external thickeners which can often be detrimental to film performance.

Pseudoplastic rheological resin for formulation of odourless stain blocking primers, basement water proofing sealers, correction fluids and intumescent coatings.

For further information regarding this product please refer to:

Christophe Baude

Tel: +33 1 6929 2733

eMail: christophe.baude@synthomer.com

Property	Typical Value	Unit	Method ¹
Solubility, Solvent KB	28		
Color	White		
Physical Form	Friable Granules		
Tg (midpoint)	60	°C	
Viscosity (Brookfield #6, 10 rpm @25°C, 20% in mixed solvent)	18	Pa.s	
Density	8.59	lb/gal	
Specific Gravity	1.03	g/cm ³	
Rheology	Pseudoplastic		

¹ internal method based upon the specified norm

Key Advantages

- Soluble in odourless Isoparaffinic solvents
- Forms tough, durable films
- Excellent adhesion without primer
- Excellent balance of sag resistance and leveling

Shipping and Storage

Available packaging : Pallet 500 Kg with 25 Kg antistatic bags

Recommended Storage conditions : Store in a dry, well ventilated area.

Shelf life : 36 months minimum from date of manufacture when stored in recommended conditions.

Product Safety

Before handling, please read the Safety Data Sheet of this product for advice on safety, use and disposal.