

Anionic fluorinated (CF₃) polyether diammonium sulfate for aqueous formulations

PolyFox PF-136A wetting, flow and leveling agent is suitable for use in a wide variety of aqueous coating, floor finish, and ink applications.

For further information regarding this product please refer to:

Jim Robbins

Tel: +1 330 794 6325

eMail: james.robbins@synthomer.com

Property	Typical Value	Unit	Method ¹
Active Ingredient	30.0	%	
pH	9.1		
Solvent Content	Water/butyl carbitol (50/50)		
Soluble in	Disperses in water in all proportions		
Ionic Character	Anionic		
Average Molecular Weight	~1400	g/mol	
Color	Colorless		
Viscosity [Brookfield]	50	cps	
Density	8.46	lb/gal	
Surface Tension	28	mN/m	

¹ internal method based upon the specified norm

Key advantages

- Improve surface appearance
- Incorporation into coating formulations results in a dramatically reduced air entrainment which reduces surface defects
- Clear and uniform in appearance
- Ability to perform both as a deaerator and as a flow and leveling agent
- Low foaming tendency

Shipping and Storage

Available Packaging: Quarts, Gallons, Pails, Drums (Plastic)

Recommended Storage Conditions : Keep Container tightly covered when not in use

Recommended Storage Temperature: 10 - 32 °C (50 - 90°F)

When stored properly, the product has a shelf life of 24 months from the date of delivery

Product Safety

Before handling, please read the Safety Data Sheet of this product for advice on safety, use and disposal.