

**25 % active Nonionic fluorinated (C2F5) polyether ethoxylated**

**PolyFox** PF-154N wetting, flow and leveling agent is suitable for use in a wide variety of aqueous coating, ink, and electronics applications.

For further information regarding this product please refer to:

Jim Robbins

Tel: +1 330 794 6325

eMail: james.robbins@synthomer.com

Property	Typical Value	Unit	Method <sup>1</sup>
Active Ingredient	25.0	%	
pH	4.2		
Soluble in	Disperses in water in all proportions		
Ionic Character	Nonionic		
Average Molecular Weight	~2900	g/mol	
Color	Colorless		
Viscosity [Brookfield]	51	cps	
Density	8.75	lb/gal	
Surface Tension	28	mN/m	

<sup>1</sup> internal method based upon the specified norm

**Key Advantages**

- Excellent water solubility with crystal clear solution for use in waterborne systems
- Coating friendly with very low foaming tendency
- very small micelle size for electronics applications
- Efficient - less than 1% add-on for most applications
- Low foaming tendency

**Shipping and Storage**

Available Packaging: Quarts, Gallons, Pails, Drums

Recommended Storage Conditions : Keep Container tightly covered when not in use

Recommended Storage Temperature: 10 - 32 °C (50 - 90°F)

When stored properly, the product has a shelf life of 24 months from the date of delivery

**Product Safety**

Before handling, please read the Safety Data Sheet of this product for advice on safety, use and disposal.