

100 % active Nonionic fluorinated (C2F5) polyether ethoxylated

PolyFox PF-159 highly efficient wetting, flow and leveling agent is suitable for use in a broad variety of aqueous, solvent, 100% solid coating, ink, and adhesive applications.

For further information regarding this product please refer to:

Jim Robbins

Tel: +1 330 794 6325

eMail: james.robbins@synthomer.com

Property	Typical Value	Unit	Method ¹
Active Ingredient	100.0	%	
pH	7.0		
Soluble in	Disperses in water in all proportions		
Ionic Character	Nonionic		
Average Molecular Weight	~3300	g/mol	
Color	Colorless		
Viscosity [Brookfield]	1220	cps	
Density	9.54	lb/gal	
Surface Tension	28	mN/m	

¹ internal method based upon the specified norm

Key Advantages

- Excellent water and solvent solubility with crystal clear solutions for use in Waterborne and solventborne systems
- Coating friendly with very low foaming tendency
- 100% solids, no VOC, no water, no cosolvent contribution
- Diol structure useful in aqueous, solvent or 100% solids formulations
- Efficient - less than 1% add-on for most applications
- Low foaming tendency

Shipping and Storage

Available Packaging: Quarts, Gallons, Pails, Drums (Plastic)

Recommended Storage Conditions : Keep Container tightly covered when not in use

Recommended Storage Temperature: 10 - 32 °C (50 - 90°F)

When stored properly, the product has a shelf life of 24 months from the date of delivery

Product Safety

Before handling, please read the Safety Data Sheet of this product for advice on safety, use and disposal.