

**Synthebond SA 134** is a soft styrene acrylic emulsion recommended as a general purpose textile back-coating and fabric finishing binder. It has some internal cross-linking and thus provides good wash and dry clean durability. The product exhibits very good water resistance.

For further information regarding this product please refer to:

Rick Pitts

Tel: +1 864-844-2379

eMail: rick.pitts@synthomer.com

Property	Typical Value	Unit	Method <sup>1</sup>
Solids	50.0	%	
Viscosity	600	cps	
pH	6.5		
Appearance	White, Emulsion		
Lbs/Gallon	8.6		
Specific Gravity	1.03		
Tg	-20	C	
Ionic Nature	Anionic		

<sup>1</sup> internal method based upon the specified norm

## Application Advice

Synthebond SA-134 may be formulated with typical water soluble, alkali soluble or associative thickeners to give required viscosity and rheology. Synthebond SA-134 can be formulated with a variety of fillers.

Synthebond SA-134 is carboxylated and may be neutralized with ammonium hydroxide or sodium salts to increase mechanical stability.

For specific formulations and procedures, contact your account representative.

## Shipping and Storage

Drums, totes, and bulk.

Keep from freezing.

## Product Safety

Before handling, please read the Safety Data Sheet of this product for advice on safety, use and disposal.