



Concrete Floor Coatings Formulated  
With **PLIOTEC™ PA05 Resins**



### Long Lasting Durability

Strong Hot Tire Pick-up  
And Chemical Resistance

[www.pliolite.com](http://www.pliolite.com)



### PLIOTEC™ PA05

Long Lasting Durability In Floor Coatings



### Excellent Water and Blush Resistance

**PLIOTEC™ PA05** resins offer exceptional water resistance, protecting surfaces from damage after application. They form a durable barrier that prevent water penetration.

### Superior Adhesion to Concrete

**PLIOTEC™ PA05** resins adhere strongly to concrete, preventing peeling, blistering, and delamination. This ensures durable and effective coatings, even in fluctuating temperatures and moist environments.

### Early Block & Abrasion Resistance

**PLIOTEC™ PA05** resins withstand heavy foot traffic and mechanical wear, maintaining surface integrity and appearance over time. This abrasion resistance is essential for floor coatings in Industrial facilities, commercial spaces, garages.



### Strong Hot-Tyre Pick-Up Resistance

Wet and dry hot-tyre pick-up resistance is a crucial feature for floor coatings, especially in areas subjected to heavy vehicle traffic. This resistance ensures that the coating remains intact and does not peel or lift when hot tires come into contact with the surface.

## Variety of Applications

- Garage floor paints
- Basement & laundry room paints
- Walkways
- Driveways
- Concrete Stains



## Additional Key Features

- Non-slip surface
- Easy maintenance
- Prevent dirt pick-up
- Easy clean-up
- APEO free

## Long-term Protection For Concrete

- Protect the concrete from aggressive agents (acids, alkalis, oils, and chemicals).
- Prevent water migration / rusting of reinforcing steel bar
- Seal the surface and prevent dust formation



Paints bearing the **PLIOTEC™** logo have passed rigorous technical specifications to ensure they meet customer requirements.

## Make Your Work Easier...

### Choose Coatings

### Formulated With PLIOTEC™ Resins!



### For More Information, Contact Your Dealer

or:

**Synthomer**

10 Greycoat Place

London SW1 1SB

United Kingdom

Email: [coatings@synthomer.com](mailto:coatings@synthomer.com)

### [www.pliolite.com](http://www.pliolite.com)

Disclaimer: This information or data, including any advice or recommendation(s) (collectively, "Information"), provided by Synthomer plc and/or its affiliates (collectively, "Synthomer") are not intended to, nor do they, constitute professional advice or services. INFORMATION IS PROVIDED ONLY AS OF THE DATE HEREOF ON AN "AS IS" AND "AS AVAILABLE" BASIS AND SYNTHOMER DOES NOT WARRANT THE ACCURACY, TIMELINESS, OR COMPLETENESS OF THE INFORMATION. TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, SYNTHOMER DISCLAIMS (I) ALL IMPLIED WARRANTIES, INCLUDING AS TO CONTINUED PRODUCTION, FITNESS FOR PARTICULAR PURPOSE, NON-INFRINGEMENT AND MERCHANTABILITY; (II) ALL LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT, OR THE RELIANCE BY ANY PARTY ON THE INFORMATION (INCLUDING INFRINGEMENT OF THIRD-PARTY INTELLECTUAL PROPERTY RIGHTS); AND (III) ALL LIABILITY, INCLUDING WITHOUT LIMITATION, FOR SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL LOSSES. Any information concerning any possible use or application of Synthomer products is given by us in good faith and it is entirely for the recipient to satisfy itself fully as to the suitability of Synthomer products for any particular purpose. Synthomer products are sold subject to Synthomer's standard terms and conditions of sale which are available from [www.synthomer.com/te](http://www.synthomer.com/te). Unless otherwise noted, Synthomer owns all right, title and interest in the information and all other intellectual property rights and data associated with this information without limitation. All trademarks and logos are the property of Synthomer. Copyright © 2026 Synthomer, all rights reserved.

Revision date: April 2026